

# CUT-OFF GRINDER SAFETY



## ERGO—STYLE GRINDER

- **FOR GRINDING OPERATIONS ONLY!**
- Too Much Torque for Use as a Cutting Tool
- Use 1/4" Grinding Wheel or Thicker
- Guard, Secondary Handle & PPE Required
- **ALWAYS** Use Two Hands to Operate Tool

## CUT-OFF GRINDER

- Proper Guard, Secondary Handle, & PPE Required
- **ALWAYS** Use Two Hands to Operate Tool
- Material **MUST** be Secured Before Cutting
- Never Force the Tool—Let It Do the Work
- Cut-off Grinder Should Only be Used if Other Alternatives Would be Just as Risky.
- **DO NOT** Use Grinder for General Demolition Work



## PERSONAL PROTECTIVE EQUIPMENT

### CUT-OFF BLADE CHOICES



- **Type 1 Original Silcer Wheels**
- .040" or .045" Thick
- **NOT ALLOWED FOR USE AT CCC**



- **Type 1 Long-Life Silcer Wheel 1/16**
- .0625" Thick
- Cut-off Grinder use **ONLY**
- **DO NOT** Use on Ergo-Style Grinder
- **Must use Type-1 Cut-off Wheel Guard Shown Below**

### TYPE-1 CUT-OFF WHEEL GUARD



- **Type 27 Depressed-Center Cutting Wheels**
- 3/32" or 1/8" Thick
- Arbor Nut, Backing Plate & Wrench Required for Wheel Installation
- Can Use Standard Open-Wheel Guard

- **HARDHAT WITH FULL-FACE SHIELD**
- **SAFETY GLASSES**
- **HEARING PROTECTION**
- **TIGHT-FITTING LEATHER OR-CUT-RESISTANT SLEEVES**
- **GLOVES**

